STAR HEADLIGHT & LANTERN CO.





63 Series

Specifications and Features

- · Long term reliability
- · Convenient compact size
- Available in a range of decibel options perfect for a wide range of vehicle applications
- Beep rate of approximately 60 per minute
- · Heavy duty polycarbonate house
- Standard 4" grommet mount (fits 4 ½" hole)
- Decibel level: sound pressure level should be selected based on the ambient noise of your work site and on regulations such as OSHA
- Standard Beep: standard single tone, familiar and widely recognized "reverse" tone
- Dual-Tone: Constant emission of sound by switching between two tones (high/low)
- Amp draw: 0.3 amps
- Dimensions: with grommet 5 %"Dia. x 1 5%"D, without grommet - 4 3/10"Dia. x 1 5/8"D

Model Numbers/Descriptions:

63-087	Single-tone, 12-36V DC, 87 db
63-097	Single-tone, 12-36V DC, 97 db
63-102	Single-tone, 12-36V DC, 102 db
63-107	Single-tone, 12-36V DC, 107 db
63-097DT	Dual-tone, 12-36V DC, 97 db
63-102DT	Dual-tone, 12V DC only, 102 db
63-707A	Auto-adjust, 12-24V DC, 77-97 db
63-802A	Auto-adjust, 12-24V DC, 82-102 db
63-807A	Auto-adjust, 12V DC only, 87-107 db

▲ Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF016 Rev C 10-26-2020







Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797



