STAR HEADLIGHT & LANTERN CO.



LDHF301 Series

LED heads are designed with optics that boost and concentrate light for maximum LED output

LDHF311 Series

Spherical LED heads are designed with diffusing optics for extremely wide angle light output

Specifications and Features

- · Self-contained, LED flashing circuitry
- S-Link System™ synchronizing capability with other Star LED units
- Spherical LED heads are designed with diffusing optics for extremely wide angle light
- Optics boost and concentrate light for maximum LED output
- Easily replace standard hide-a-way remote strobe tubes with 1" mounting holes
- Nickel plated aluminum housing allow for our advanced thermal heat management
- Customer changeable colored lenses (with White kit only), giving these LED lights versatility in the field
- 25 customer selectable flash patterns
- Amp draw: 0.5 amps per head (max)
- Voltage: 12-24V DC
- Lens colors:

Model Numbers/Descriptions:

LDHF301-*-10	Directional optics, 10' cable
LDHF301-*-30	Directional optics, 30' cable
LDHF311-*-10	Spherical optics, 10' cable
LDHF311-*-30	Spherical optics, 30' cable

SF030 Rev G 2-26-2016





Star Headlight & Lantern Co., Inc. 455 Rochester Street

Avon, NY 14414
Phone: 585-226-9500
Fax: 888-478-2797
starheadlight.com





STAR HEADLIGHT & LANTERN CO.



LDK302 Series

LED heads are designed with optics that boost and concentrate light for maximum LED output



LDK312 Series

Spherical LED heads are designed with diffusing optics for extremely wide angle light output

Specifications and Features

- · Self-contained, LED flashing circuitry
- S-Link System™ synchronizing capability with other Star LED units
- LED heads are designed with diffusing optics for extremely wide angle light
- Optics boost and concentrate light for maximum LED output
- Easily replace standard hide-a-way remote strobe tubes with 1" mounting holes
- Nickel plated aluminum housing allow for our advanced thermal heat management
- Customer changeable colored lenses (with White kit only), giving these LED lights versatility in the field
- 20 customer selectable flash patterns
- Amp draw: 0.5 amps per head (max)
- Voltage: 12-24V DC

Cable Lengths: SWH-L* (* = 4', 8', 15', 20', 25', 30', 35')

Model Numbers/Descriptions:

LDK302	(1) flasher module, (1) 4' cable with attached connectors, (1) 8' cable with attached connectors, (2) LED head assemblies with 2' leads and attached connectors
LDK304	(2) flasher module, (2) 4' cable with attached connectors, (2) 8' cable with attached connectors, (4) LED head assemblies with 2' leads and attached connectors
LDK312	(1) flasher module, (1) 4' cable with attached connectors, (1) 8' cable with attached connectors, (2) LED head assemblies with 2' leads and attached connectors
LDK314	(2) flasher module, (2) 4' cable with attached connectors, (2) 8' cable with attached connectors, (4) LED head assemblies with 2' leads and attached connectors





Star Headlight & Lantern Co., Inc.

455 Rochester Street Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797 starheadlight.com



