## 203MVL, 204MVL









204MVL

## **FEATURES & BENEFITS**

- Two Star Generation IV LEDs
- Twenty-six customer selectable flash patterns, including Steady-On and Cycle All
- Long life LEDs, rated for up to 100,000 hours
- Compact and powerful LED light output
- External pattern select wire (permanent mount only)
- Twist on/off lens
- Durable ABS plastic base
- Durable polycarbonate lens
- Flange permanent mount or magnet mount

- Durable polycarbonate lens
- Flange permanent mount, or magnet mount (203MVLM)
- Pipe mount no longer available for 204MVL
- Voltage: 10-110V DC
- Amp draw: 0.35 amps @ 12V DC, 0.13 amps @ 110V DC
- Colors:
- Approvals 203MVL: SAE Class II (Amber)\*, SAE Class III (Blue, Red, White)\*
- Approvals 204MVL: SAE Class II (Amber)\*,
- \* does not apply to all flash patterns

PART	DESCRIPTION
203MVL	3 ½"H, LED Beacon, flange mount, 10-110V DC
203MVLM	3 ½"H, LED Beacon, magnet mount with cig. plug, 10-110V DC
204MVL	5"H, LED Beacon, flange mount, 10-110V DC

▲ Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF092 Rev-K 1-3-24



STAR
Safety Technologies by Grote