



STAR HEADLIGHT & LANTERN CO.

240HL



240HSL



240HSFL



240HCL

Specifications and Features

- Star Halo® technology is patented (#8,662,702)
- 12 different selectable flash patterns in either of two phases, plus steady-on
- S-Link System™ synchronizing capabilities with other Star LED units
- Fully encapsulated circuitry for weather and shock resistance
- Extremely low current draw
- Durable polycarbonate lens
- Rugged die-cast aluminum base is fully gasketed
- Permanent mount base with 1" pipe mount, flange mount, optional magnet mount with cig. plug (on/off switch and pattern select)
- Dimensions: tall dome - 6"H x 5 1/2"Dia., short dome - 4 1/4"H x 6"Dia.
- Voltage: permanent mount - 10-30V DC, magnet mount - 10-16V DC
- Amp draw: 0.6 amps @ 12V DC, 0.3 amps @ 24V DC
- Lens colors:
- LED colors (H8L):
- LED colors (HL):
- Approvals: Exceeds SAE Class I J845 standards, California Title 13 available

Model Numbers/Descriptions:

240H8AFL	Halo®, ultra high intensity, eight LEDs, flange base with 1" pipe mount, tall lens with dust cover
240H8AL	Halo®, ultra high intensity, eight LEDs, permanent mount base with 1" pipe mount, tall lens with dust cover
240H8ALM	Halo®, ultra high intensity, eight LEDs, magnet mount, dust cover
240H8CFL	Halo®, ultra high intensity, eight LEDs, flange base with 1" pipe mount, tall lens
240H8CFL-G	Halo®, ultra high intensity, eight LEDs, flange base with 1" pipe mount, tall lens, branch guard
240H8CL	Halo®, ultra high intensity, eight LEDs, permanent mount base with 1" pipe mount, tall lens
240H8CLM	Halo®, ultra high intensity, eight LEDs, magnet mount, tall lens
240H8SFL	Halo®, ultra high intensity, eight LEDs, flange base with 1" pipe mount, short lens
240H8SGL	Halo®, ultra high intensity, eight LEDs, G-plate with 1/2" pipe mount, tall lens
240H8SL	Halo®, ultra high intensity, eight LEDs, permanent mount base with 1" pipe mount, short lens
240H8SLM	Halo®, ultra high intensity, eight LEDs, magnet mount, short lens
240HCFL	Halo®, high intensity, four LEDs, flange base with 1" pipe mount, tall lens
240HCFL-G	Halo®, high intensity, four LEDs, flange base with 1" pipe mount, tall lens, branch guard
240HCGL	Halo®, high intensity, four LEDs, G-plate with 1/2" pipe mount, tall lens
240HCL	Halo®, high intensity, four LEDs, permanent mount base with 1" pipe mount, tall lens
240HCLM	Halo®, high intensity, four LEDs, magnet mount, tall lens
240HSFL	Halo®, high intensity, four LEDs, flange base with 1" pipe mount, short lens
240HSGL	Halo®, high intensity, four LEDs, G-plate with 1/2" pipe mount, short lens
240HSL	Halo®, high intensity, four LEDs, permanent mount base with 1" pipe mount, short lens
240HSLM	Halo®, high intensity, four LEDs, magnet mount, short lens

SF106 Rev B 9-20-2016

STAR
WARNING
SYSTEMS®

STAR SIGNAL
VEHICLE PRODUCTS®

Star Headlight & Lantern Co., Inc.

455 Rochester Street
Avon, NY 14414
Phone: 585-226-9500
Fax: 888-478-2797
starheadlight.com

BRADFORD
Vehicle Solutions Inc.™



PROUDLY MADE IN THE U.S.A.
An ISO 9001:2008 Certified Company