



SS670

FEATURES & BENEFITS

- User can easily retrofit any, old siren harness with only a wire stripper and screw driver
- 26 Programmable siren tones including
- 2 Approved yelp tones
- Simulated mechanical wail & manual
- 8 Air horn tones
- 7 Position audio tone function select knob
- Self-resetting circuit protection against speaker shorts
- Integrated public address microphone, volume adjustable from front of siren
- LED diagnostics allow quick trouble shooting
- On/off rocker switch
- Auxiliary enable can be used to enable a siren/air horn tone; or for hands free tone cycling
- Two-way radio rebroadcast volume adjustable from front of siren
- Reverse polarity protection
- Push button on back of unit allows the user to customize the tones
- Built-in fuse
- High and low voltage shutdown protection
- Reverse polarity protection
- Ships complete with positive locking connector, mic clip, mounting bracket, hardware, and instructions
- Dimensions: 2"H x 6"W x 4¹¹/₁₆"D
- Output: 100 watts (1 speaker)
- Voltage: 10-16V DC
- Frequency: 675-3000Hz
- Amp draw: 8 amps
- Stand-by current switch off: 0.004A
- Approvals: Exceeds acoustical and environmental requirements, SAE J1849 California Title 13.

PART	DESCRIPTION
SS670-013	Full function 100 watt siren with PA and Radio Repeat

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF047 Rev-E 05-11-2023



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*