STAR HEADLIGHT & LANTERN CO.

New & Improved All push button control head





Specifications and Features

- Trunk mount amplifier with remote control head
- Air Horn, Manual, cycle through Wail, Yelp, Phaser (or two tone)
- Up to four push button 20 amp lighting outputs & three progressive push button outputs
- Eight light functions
- · Integrated public address microphone
- Dual color backlighting on keypad (Amber and Red)
- Traffic Director Compatibility:

By default the S4 button will cycle through the Left, Right, and Center-Out patterns of compatible Traffic Directors. Optionally, the S3 button can be programmed to activate the Warn pattern of your compatible Traffic Director. (note: compatible with Star Phazer, ULB48, ULB38, DLQS or dummy head sticks in conjunction with the TDC-3 flasher)

- Positive or negative switching for auxiliary and park kill inputs
- · LED speaker diagnostics
- · High and low voltage shut down protection
- Self-resetting circuit protection against speaker shorts
- Dimensions: Control head: 6"H x 2 ½" W x ¹⁵/₁₆"D, Amp: 2 ½"H x 7"W x 7 ¾"D
- · Weight: 8.5 lbs.
- Output: 100 or 200 watts (one or two speakers)
- Input: 10-16V DC
- Siren tone frequency: 675-1633Hz
- Amp Draw: 8 amps (per speaker)
- Approvals: Exceeds Acoustical and Environmental requirements of SAE J1849, CA Title 13 (when used with SVP driver(s) and approved tones)

Model Numbers/Descriptions:

LCS880-016 | Full feature handheld siren with light controls, traffic director function, cradle, siren amplifier

SF186 Rev - 4-21-2017





455 Rochester Street
Avon, NY 14414
Phone: 585-226-9500
Fax: 888-478-2797

starheadlight.com

IIIBRADFORD™ Vehicle Solutions Inc.

