



LCS880-016



FEATURES & BENEFITS

- Trunk mount amplifier with remote control head
- Air Horn, Manual, cycle through Wail, Yelp, Phaser (or two tone)
- Up to four push button 20 amp lighting outputs and three progressive push button outputs
- Eight light functions
- Integrated public address microphone
- Dual color backlighting on keypad (Amber and Red)
- **Traffic Director Compatibility:**
By default the S4 button will cycle through the Left, Right, and Center-Out patterns of compatible Traffic Directors. Optionally, the S3 button can be programmed to activate the Warn pattern of your compatible Traffic Director. (note: compatible with Star Phaser, ULB48, ULB38, DLQS or dummy head sticks in conjunction with the TDC-3 flasher)

- Positive or negative switching for auxiliary and park kill inputs
- LED speaker diagnostics
- High and low voltage shut down protection
- Self-resetting circuit protection against speaker shorts
- Dimensions:
Control head: 6"H x 2 1/2"W x 15/16"D
Amp: 2 1/2"H x 7"W x 7 3/8"D
- Weight: 8.5 lbs.
- Output: 100 or 200 watts (one or two speakers)
- Input: 10-16V DC
- Siren tone frequency: 675-1633Hz
- Amp Draw: 8 amps (per speaker)
- Approvals: Exceeds Acoustical and Environmental requirements of SAE J1849, CA Title 13 (when used with SVP driver(s) and approved tones)

PART	DESCRIPTION
LCS880-016	Full feature handheld siren with light controls, traffic director function, cradle, siren amplifier

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF186 Rev- 11-29-2023



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*