

LCS800, LCS850

STAR
Safety Technologies by *Grote*



LCS850-8



LCS800-008

FEATURES & BENEFITS

- Trunk mount amplifier with remote control head
- Wail, Yelp, Air Horn, Phaser, Manual, and Two-Tone
- Eight light functions
- Four position progressive slide switch with LED indicators
- Integrated public address microphone
- Dual color backlighting on keypad (Amber and Red)
- Park kill input, auxiliary input
- Positive or negative switching for auxiliary and park kill inputs
- Replaceable jumpers and dip switches for option selection
- Universal mounting bracket or flange mount available
- Drives one or two 100 watt speakers
- LED speaker diagnostics
- High and low voltage shut down protection
- Self-resetting circuit protection against speaker shorts
- Ships complete with positive locking connector, mic. clip, mounting bracket, hardware, thirty standard function replacement labels, RFI filter, and instructions
- Dimensions LCS800 and LCS850: Control head with flange: 4¹¹/₆₄"H x 7¹¹/₁₆"W x 7⁷/₈"D, Control head without flange: 3³/₁₆"H x 6¹¹/₁₆"W x 7⁷/₈"D, Amp: 2 1/2"H x 7"W x 7³/₈"D (plus 3/4" flange on each side)
- Weight: LCS800, LCS800-F (with flange) - 8.5 lbs
LCS850, LCS850-F (with flange) - 9.5 lbs
- Output: 100 or 200 watts (one or two speakers)
- Input: 10-16V DC
- Siren tone frequency: 675-1633Hz
- Amp Draw: 8 amps (per speaker)
- Approvals: Exceeds Acoustical and Environmental requirements of SAE J1849, CA Title 13 (when used with SVP driver(s) and approved tones)

PART	DESCRIPTION
LCS800-008	Siren with light control
LCS800-8F	Siren with light control, with flange
LCS850-8	Siren with light and arrow stick controller
LCS850-8F	Siren with light and arrow stick controller, with flange

 **Warning:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF049 Rev-D 05-11-2023



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*