



SPECIFICATIONS

Typical Input Voltage Range: 10-16 VDC
 Typical Current Draw: 2.7 A @ 12VDC Incandescent
 4.0 A @ 12VDC Halogen
 Approval: SAE J845 Class 1 Amber, Blue, Clear, Red
 Flash Rate: Standard 80fpm/High speed 160fpm
 Available 120fpm
 Output Power: Incandescent 35W, Halogen 50W
 Connections: 18" Min. wires exiting the unit.
 Permanent Mounting: 2 Hole "3.50" center & 1/2 npt Pipe
 Dimensions: (Tall Dome): 7.00" tall x 6.00"
 Individual Shipping weight: 2.0 lbs.

REV.	ECR	DESCRIPTION	DATE
-	713	INITIAL DRAWING REQUEST	07/30/96
A	816	20RH TO 20RH	10/02/96
B	8592	ADDED NEW DRAWING FORMAT NOTES & SCART4000	09/09/09
C	11882	ADDED SPECIFICATIONS: MOUNT PARTS, WIRE FUNCTION NOTE	04/07/14

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES Dial Tolerances ± 0.003 Angular: ± 2 DEG. X ± .100 XX ± .020 XXX ± .005 XXXX ± .001		DRAWN BY: DPL DRAWING APPROVED BY ECR	
ROHS COMPLIANT: NA		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAR HEADLIGHT & LANTERN CO., INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAR HEADLIGHT & LANTERN CO., INC. IS STRICTLY PROHIBITED.	
MATERIAL: NA		TITLE: MODEL DRAWING	
FINISH: NA		95 & 150 FPM HALOGEN REVOLVING WARNING LIGHT	
SCALE: 1:1		DWG. NO. 20RH	
DO NOT SCALE FROM DRAWING		REV C	
SHEET 1 OF 1			

- NOTES:**
- 1) INSTRUCTION SHEET: P/N PLITSTR43
 - 2) PACKING: SCART4000
UNIT BOX P/N PCART4000UN
BOX INSERT P/N PCART4000CS
POLY BAG P/N P30024-12
BOX LABEL BLANK P/N PLABSTR
 - 3) DOME * = A, B, C, R

STAR HEADLIGHT & LANTERN CO., INC.
 455 ROCHESTER ST. AVON NY 14414
 Ph: (585) 226-9500 Fax: (585) 226-2029