

MICRO-STAR[®] LED LIGHT

STAR
Safety Technologies by *Grote*



DLITE



DLITS



50° Spread



15° Spread



S30019-317
Bezel (included)



S30019-320
Reverse Bezel
(Sold Separate)



274-DLIT-RL



274-DLIT-45



274-DLIT-LPB4



274-DLIT-RT



274-DLIT-U



274-DLIT-CLP



274-DLIT-W



30019-314 Shim kit



side view



top view

FEATURES & BENEFITS

- Ultra low profile
- Six super bright Star Generation V LEDs
- 12 different selectable flash patterns in either of two phases, plus steady-on
- New base w/o mounting ears allows sealed light to be independent from mounting stress forces by "floating" under mounting bezel
- Ultrasonic weld fuses lens to plastic base providing maximum weather tight seal
- Single and split color models
- Current limit protection over entire operating voltage

- Standard four wire hook-up
- S-Link System™ synchronizing capabilities with other Star LED units
- Dimensions: 1" H x 4 3/16" W x 25/64" D
- Voltage: 10-30V DC
- Amp draw: 0.75 amps
- Color availability:
- Split colors:
- Approvals: SAE Class I, CA Title 13 available where applicable
* approvals only apply when properly configured

PART	DESCRIPTION
DLITE-**	Six array LED head, wide spread optic
DLITS-**	Six array LED head, spot spread optic
274-DLIT-RL	License plate bracket for two DLIT's
274-DLIT-CLP	Hood clip bracket mounting for DLIT's
274-DLIT-RT	Adhesive bracket for DLIT's

PART	DESCRIPTION
274-DLIT-LPB4	License plate bracket for four DLIT's
274-DLIT-45	45 Degree bracket for DLIT's
274-DLIT-U	Universal bracket for DLIT's
274-DLIT-W	Window adhesive bracket for DLIT's
30019-314	Shim Kit

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF172 Micro Star DLIT Rev K 11-27-23



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*

MICRO-STAR® LED LIGHT

STAR
Safety Technologies by *Grote*



FEATURES & BENEFITS

- Ultra low profile
- Three super bright Star Generation V LEDs
- 12 different selectable flash patterns in either of two phases, plus steady-on
- Robust design, die cast aluminium base
- Endless mounting possibilities
- Current limit protection over entire operating voltage
- S-Link System™ synchronizing capabilities with other Star LED units
- Dimensions: 1" H x 3 1/16" W x 7/16" D
- Voltage: 10-16V DC
- Amp draw: 0.3 amps
- Color availability:
- Approvals:
DLIT3E: SAE Class II (amber, blue, red, white)
DLIT3S: SAE Class I (amber, blue, red, white)
* approvals only apply when properly configured

PART	DESCRIPTION
DLIT3E-*	Three array LED head, wide spread optic
DLIT3S-*	Three array LED head, spot spread optic
274-DLIT3-U	Universal bracket for DLIT3's

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF172 Micro Star DLIT Rev K 11-27-23



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*