



STAR HEADLIGHT & LANTERN CO.

DLQS QUICK STICK SERIES



Specifications and Features



- Weatherproof interior or exterior mount
- 34 customer selectable warning flash patterns plus 5 phase options
- 12 traffic director patterns, TD models come with SB44-5 control box (6 and 8 head versions only)
- DLQS-4 comes with a 2' three-wire cable (power, ground, pattern select)
- DLQS3-6-**-3 & DLQS3-8-**-3 comes with 3' six wire cable
- DLQS-6 (8) & DLQS3-6 (8) comes with a 25' six wire cable, (power, ground, program wire, left enable, right enable, warn enable, center-out = L + R)
- Bottom and rear T-slots allow for easy mounting via industry standard #10 carriage bolt
- Front load assembly design allows quick and easy swap of heads
- Built-in Traffic Director function available (six head and eight head models only)
- Sealed DLITS heads for maximum reliability
- Shipped standard with L-brackets
- Dual Warn option (8 head module only): Programmable to allow the end heads to flash a warning pattern, while the center 6 heads flash a traffic director pattern
- SB44-5 can be purchased separately

DLQS-76

- Ideal for front push bumpers, rear SUV or pickup truck windows, headache rack, and running board lights
- Dimensions:
 - (DLQS3-6) 19 1/4" L x 1 15/32" W x 1 3/16" H
 - (DLQS3-8) 25 1/2" L x 1 15/32" W x 1 3/16" H
 - (DLQS-4) 20 1/2" L x 1 15/32" W x 1 3/16" H
 - (DLQS-6) 30 39/64" L x 1 15/32" W x 1 3/16" H
 - (DLQS-8) 40 39/64" L x 1 15/32" W x 1 3/16" H
 - (DLQS-47) 47" L x 1 15/32" W x 1 3/16" H
 - (DLQS-56) 56" L x 1 15/32" W x 1 3/16" H
 - (DLQS-76) 76" L x 1 15/32" W x 1 3/16" H
- Voltage: 10-16V DC
- Amp draw: 2 amps average (4 head) and (DLQS3 versions) 3 amps average (6 head) 4 amps average (8 head)
- Color combinations:
- Approvals: SAE Class 1 (A,B,C,R DLITS only)



SB44-5



Model Numbers/Descriptions:

DLQS3-6-**-3	19" Six LED heads, with traffic director function and 3' cable
DLQS3-6	19" Six LED heads, with traffic director function and 25' cable
DLQS3-8-**-3	25" Eight LED heads, with traffic director function and 3' cable
DLQS3-8	25" Eight LED heads, with traffic director function and 25' cable
DLQS-4	20.5" Four LED heads and 25' cable
DLQS-6	30.6" Six LED heads, with traffic director function and 25' cable
DLQS-6-AA-TD	30.6" Six LED heads, with traffic director function, SB44-5 and 25' cable
DLQS-8	40.6" Eight LED heads, with traffic director function and 25' cable
DLQS-8-AA-TD	40.6" Eight LED heads, with traffic director function, SB44-5 and 25' cable
DLQS-47	47" Eight LED heads, with traffic director function and 25' cable
DLQS-56	56" Six LED heads, with traffic director function and 25' cable
DLQS-76	76" Eight LED heads, with traffic director function and 25' cable

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF190 Rev G 09-09-2021



Star Headlight & Lantern Co., Inc.
 455 Rochester Street
 Avon, NY 14414
 Phone: 585-226-9500
 Fax: 888-478-2797
starheadlight.com



PROUDLY MADE IN THE U.S.A.
 An ISO 9001:2015 Certified Company