



# STAR HEADLIGHT & LANTERN CO.

## X-FIRE™ LED LIGHTS



**PATENT  
PENDING**

### Specifications and Features

- Star X-Fire™ technology
- 12 different selectable flash patterns in either of two phases, plus steady-on
- Exceeds SAE Class I J845 standards
- S-Link System™ synchronizing capabilities with other Star LED units, hardwire only
- Extremely low current draw
- Durable polycarbonate, twist on/off lens
- Lightweight polycarbonate, universal flange base: three-hole, permanent mount, 1" pipe mount, optional vacuum magnet mount or standard magnet mount with cig. plug (on/off and pattern select)
- Dimensions (tall dome) 6 11/16"H x 6 13/32"Dia., (short dome) 4 3/4"H x 6 13/32"Dia.
- Voltage: perm. mount - 9-32V DC, mag. mount - 9-16V DC
- Amp Draw: 0.5 amps @ 12V DC, 0.3 amps @ 24V DC
- Lens colors:
- LED colors with clear dome:
- Approvals: SAE Class I (amber short and tall)

### Model Numbers/Descriptions:

|          |  |
|----------|--|
| 266TCL   | Class I, tall lens, three hole permanent mount   |
| 266TCLM  | Class I, tall lens, magnet mount                 |
| 266TCLV  | Class I, tall lens, vacuum magnet mount          |
| 266TCFL  | Class I, tall lens, flange base permanent mount  |
| 266TCLFL | Class I, tall lens, less flange 1" pipe mount    |
| 266TSL   | Class I, short lens, three hole permanent mount  |
| 266TSLM  | Class I, short lens, magnet mount                |
| 266TSLV  | Class I, short lens, vacuum magnet mount         |
| 266TSFL  | Class I, short lens, flange base permanent mount |
| 266TSLFL | Class I, short lens, less flange 1" pipe mount   |

SF192 REV- 9/22/17

**STAR**  
WARNING  
SYSTEMS®

**STAR SIGNAL**  
VEHICLE PRODUCTS®

**Star Headlight & Lantern Co., Inc.**

455 Rochester Street  
Avon, NY 14414

Phone: 585-226-9500

Fax: 888-478-2797

starheadlight.com



**BRADFORD**  
Vehicle Solutions Inc.



PROUDLY MADE IN THE U.S.A.  
An ISO 9001:2008 Certified Company