

X-FIRE® LED BEACON 266T*L

STAR
Safety Technologies by Grote



FEATURES & BENEFITS

- Star X-Fire® technology
- Twelve different selectable flash patterns in either of two phases, plus Steady-On
- Exceeds SAE Class I standards
- S-Link System™ synchronizing capabilities with other Star LED units, hardwire only
- Extremely low current draw
- Durable polycarbonate, twist on/off lens
- Permanent mount options: Lightweight polycarbonate base with three-holed flange and 1" pipe mount or two-holed flange and 1" pipe mount
- Magnet mount options: Cig. plug (On/Off and Pattern Select) with either standard magnet or vacuum magnet
- Dimensions:
Tall dome - 6 11/16" H x 6 13/32" Dia.
Short dome - 4 7/8" H x 6 13/32" Dia.
- Voltage: perm. mount - 9-32V DC, mag. mount - 9-16V DC
- Amp Draw: 0.5 amps @ 12V DC, 0.3 amps @ 24V DC
- Lens colors: Yellow Blue Green Red Clear
- LED colors with Clear dome: Yellow Clear
- Approvals: SAE Class I (Amber short and tall)

PART	DESCRIPTION
266TAL	Class I, tall lens, dust cover, three hole, permanent mount
266TASL	Class I, short dome, dust cover, three hole, permanent mount
266TCFL	Class I, tall lens, flange base, permanent mount
266TCL	Class I, tall lens, three hole permanent mount
266TSFL	Class I, short lens, flange base, permanent mount
266TSL	Class I, short lens, three hole permanent mount
266TCLM	Class I, tall lens, magnet mount
266TSLM	Class I, short lens, magnet mount
266TCLV	Class I, tall lens, vacuum magnet mount
266TSLV	Class I, short lens, vacuum magnet mount

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF192 REV-A 09-07-2023



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by Grote