STAR SINCE ®

STAR HEADLIGHT & LANTERN CO.



Specifications and Features

- Star X-Fire[™] technology
- 12 different selectable flash patterns in either of two phases, plus steady-on
- Exceeds SAE Class I J845 standards
- S-Link System™ synchronizing capabilities with other Star LED units, hardwire only
- · Extremely low current draw
- Fully gasketed between the durable polycarbonate dome and base
- Two internal V-mirrors, enhance flashes
- Magnet mounts include vinyl pads to avoid scratching the surface
- Permanent mount selectable flash patterns via external pattern select wire, 24" leads

- Magnet and Vacuum magnet mount selectable flash patterns via switch on cig. plug and separate on/off switch
- · Extremely low current draw
- Dimensions: 4 ½"H x 16 1/8"W x 7 1/4"D
- Voltage: permanent mount 12-24V DC, magnet mount - 12V DC
- Amp draw: 1.2 amps @ 12V DC, 0.6 amps @ 24V DC
- Dome colors:
 Inner lens colors:
- Approvals SAE J845 Class I, California Title 13*,
 (Amber Dome) * does not apply to all flash patterns

Model Numbers/Descriptions:

9200LX	X-Fire™, SAE Class I, California Title 13, LED mini-bar, permanent mount
9200LXM	X-Fire™, SAE Class I, California Title 13, LED mini-bar, magnet mount
9200LXV	X-Fire™, SAE Class I, California Title 13, LED mini-bar, vacuum magnet mount

SF208 Rev - 1-10-2019





Star Headlight & Lantern Co., Inc. 455 Rochester Street

Avon, NY 14414
Phone: 585-226-9500
Fax: 888-478-2797
starheadlight.com



