



STAR HEADLIGHT & LANTERN CO.

DLQSMC MULTI COLOR QUICK STICK SERIES




DLQSMC-8



Specifications and Features

- Weatherproof interior or exterior mount
- 36 customer selectable warning flash patterns plus 5 phase options
- 10 traffic director patterns (6 and 8 head versions only)
- DLQSMC-6 (8) comes with a 25' six wire cable, Default configuration: (flashing color 1, flashing color 2, pattern select, cruise, left, right)
Note: enable left & right for center out
- Bottom and rear T-slots allow for easy mounting via industry standard #10 carriage bolt
- Front load assembly design allows quick and easy swap of heads
- Built-in Traffic Director function available (six head and eight head models only)
- Sealed DLIT heads for maximum reliability
- Shipped standard with L-brackets
- Dual Warn option (8 head module only): Programmable to allow the end heads to flash a warning pattern, while the center 6 heads flash a traffic director pattern
- Enables are Programmable for Cruise, Steady burn, or Flashing
- Ideal for front push bumpers, rear SUV or pickup truck windows, headache rack, and running board lights
- Dimensions:
(DLQSMC-4) 20 1/2" L x 1 15/32" W x 1 3/16" H
(DLQSMC-6) 30 39/64" L x 1 15/32" W x 1 3/16" H
(DLQSMC-8) 40 39/64" L x 1 15/32" W x 1 3/16" H
- Voltage: 10-16V DC
- Amp draw: 2 amps average (4 head)
3 amps average (6 head) 4 amps average (8 head)
- Color combinations for each head:

White	Green	Red	Blue	Yellow	Red
Green	Orange	Red	Blue	Yellow	Red
Green	Orange	Red	Blue	Yellow	Red
- Approvals: SAE Class I (A,B,C,R)



Model Numbers/Descriptions:

DLQSMC-4	20.5" Four LED heads
DLQSMC-6	30.6" Six LED heads, with traffic director function
DLQSMC-8	40.6" Eight LED heads, with traffic director function



Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF 212 Rev A 11-12-2019



Star Headlight & Lantern Co., Inc.
455 Rochester Street
Avon, NY 14414
Phone: 585-226-9500
Fax: 888-478-2797
starheadlight.com



PROUDLY MADE IN THE U.S.A.
An ISO 9001:2015 Certified Company