

# **SPECIFICATIONS:**

OPERATING VOLTAGE RANGE: 10-16VDC NOMINAL VOLTAGE: 12V CURRENT DRAW: DLQSMC-4: MAX = 3.8A, AVERAGE = 1.9A DLQSMC-6: MAX = 5.6A, AVERAGE = 2.8A DLQSMC-8: MAX = 7.5A, AVERAGE = 3.8A OPERATING TEMPERATURE RANGE: -22F (-30C) TO 122F (50C)

## **CONNECTIONS:**

8-WIRE CABLE, LENGTH 25FT 18 GAGE RED WIRE (IGNITION SWITCH +12VDC)

18 GAGE BLACK WIRE (- GROUND)

22 GAGE PINK WIRE (PRIORITY 5 FUNCTION) -- TAKEDOWNS (Color 2) (4-HEAD STICK), CRUISE (Color 1) (6 & 8-HEAD STICK) 22 GAGE WHITE W/BROWN WIRE (PRIORITY 4 FUNCTION) -- FLASHING/WARN COLOR 1 (4-HEAD STICK), LEFT ARROW (Color 1), (6 & 8-HEAD STICK) 22 GAGE GREEN W/YELLOW WIRE (PRIORITY 3 FUNCTION) -- FLASHING/WARN COLOR 2 (4-HEAD STICK), RIGHT ARROW (Color 1), (6 & 8-HEAD STICK) 22 GAGE ORANGE W/RED WIRE (PRIORITY 2 FUNCTION) -- DUAL COLOR FLASHING/WARN (4-HEAD STICK), RIGHT ARROW (Color 1), (6 & 8-HEAD STICK) 22 GAGE YELLOW WIRE (PRIORITY 2 FUNCTION) -- DUAL COLOR FLASHING/WARN (4-HEAD STICK), FLASHING/WARN (Color 1), (6 & 8-HEAD STICK) 22 GAGE YELLOW WIRE (PRIORITY 1 FUNCTION) -- CRUISE (Color 1) (4-HEAD STICK,)FLASHING/WARN (4-HEAD STICK), FLASHING/WARN (Color 2), (6 & 8-HEAD STICK) 22 GAGE RED W/GREEN (PATTERN/PROGRAMING) -- PATTERN OR PHASE SELECT (4, 6 & 8-HEAD STICK) 20 GAGE RED W/GREEN (PATTERN/PROGRAMING) -- PATTERN OR PHASE SELECT (4, 6 & 8-HEAD STICK)

22 GAGE BARE (DRAIN/SHIELD)

## INSTALLATION:

BACK AND BOTTOM SLOTS (DESIGNED FOR #10 CARRIAGE BOLT) MOUNTING BRACKET: 14GA COLD ROLLED STEEL, POWDER COATED CARRIAGE BOLT #10-32, STAINLESS STEEL FLAT WASHER #10, ZINC PLATED HEX SERRATED FLANGE NUT #10-32, STAINLESS STEEL

#### **MATERIALS:**

HOUSING: EXTRUDED BLACK ANODIZED ALUMINUM LENS: POLYCARBONATE

## **CERTIFICATIONS:**

SAE J595 MAR2014 CLASS 1 (SPOT OPTICS ONLY, ALL COLORS BUT GREEN)

## PRODUCT LABEL:

WHITE POLYESTER STOCK 2" X 1"

# **INSTRUCTION SHEET:**

1 PROVIDED (ENGLISH)

UNLESS OTHERWISE SPECIFIED	DRAWN BY:	EP	STAR HI	EADLIGHT & LANTE	RN CO	
DIMENSIONS ARE IN INCHES	DRAWING APPROVED BY ECR		455 Rochester St. Avon NY 14414 Ph:(585) 226-9500 Fax: (585) 226-2029			
TOLERANCES:	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAR HEADLIGHT & LANTERN CO., INC., ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAR HEADLIGHT & LANTERN CO., INC, IS STRICTLY PROHIBITED.					
ANGULAR: ± 2 DEG. .X ± .100 .XX ± .020 .XXX ± .005			MODEL: DLQSMC-4, DLQSMC-6 and DLQSMC-8			
.XXXX ± .001 RoHS COMPLIANT: Yes			MODEL DRAWING			
MATERIAL: N/A			DWG. NO.	DLQSMC		REV -
FINISH: N/A			SCALE: 1:16	DO NOT SCALE FROM DRAWING	SHEET	1 OF 1

COLOR 1	COLOR 2		
BLUE	WHITE		
GREEN	WHITE		
RED	WHITE		
AMBER	WHITE		
AMBER	GREEN		
AMBER	RED		
AMBER	BLUE		
RED	BLUE		
RED	GREEN		