



SB44-8



PROGRAMMABLE SWITCHES

Specifications and Features

- 8-button control panel for operating up to 8 lights/ devices
- Red backlit silicone rubber keypad with 14 programmable brightness settings
- Programmable switching options: Ground-side switching, Momentary switching, Normally Closed, Flashing Output with Phase settings, and Audio feedback
- Option to program as a stand-alone Traffic Director Controller for logic-controlled sticks
- Smartphone Programmable
- Durable polycarbonate housing
- · Includes 12-pin wire harness to simplify installation
- 274-SB44-H (SB44-5 not included)
 - - ⁾ 274-SB44-U

- Includes aluminum U-bracket (274-SB44-U) and stainless steel hardware for versatile mounting
- Includes replaceable velvet finish Lexan[™] button labels
- Dimensions: 2 5/8"H x 4 1/8 "W x 1/2"D
- Operating range: 9-16V DC
- Operating temperature range: -40°F to 131°F
- 6 outputs at 2.5A average (5 A peak)
- 2 outputs at 0.06A average



274-SB44-VC



Model Numbers/Descriptions:

IFIN

VEHICLE PRODUC

SB44-8	Programmable switchbox, 8 buttons, U-bracket included
274-SB44-H	Headliner Bracket
274-SB44-U	U-Bracket
274-SB44-ULP	Low profile U-Bracket
274-SB44-VC	Visor Clip Bracket

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



Star Headlight & Lantern Co., Inc. 455 Rochester Street Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797 starheadlight.com



PROUDLY MADE IN THE U.S.A. An ISO 9001:2015 Certified Company

SF223 Rev-A 1-13-2022

STAR HEADLIGHT & LANTERN CO. 1880 AUX TARSIGNAL POWER WARN SB44-5 **PROGRAMMABLE SWITCHES**

Specifications and Features

- 5-button standard Traffic Director control option and auxiliary switches
- Built-in LED display mimics Traffic Director output
- Red backlit silicone rubber keypad with 14 programmable brightness settings
- Option to program as a 4-output switchbox
- Durable polycarbonate housing
- · Hardwired 11" pigtail

- Includes aluminum U-bracket (274-SB44-U) and stainless steel hardware for versatile mounting
- Includes replaceable velvet finish Lexan[™] button labels
- Dimensions: 2 ⁵/₈"H x 4 ¹/₈ "W x ¹/₂"D
- Operating range: 9-16V DC
- Operating temperature range: -40°F to 131°F
- 2 outputs at 2.5A average (5 A peak)
- 2 outputs at 0.06A average





(SB44-5 not included) 274-SB44-U



274-SB44-VC



Model Numbers/Descriptions:

GA

VEHICLE PRODUCTS

SB44-5	Programmable switchbox, 5 buttons, U-Bracket included
274-SB44-H	Headliner Bracket
274-SB44-U	U-Bracket
274-SB44-ULP	Low profile U-Bracket
274-SB44-VC	Visor Clip Bracket

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF223 Rev-A 1-13-2022



Star Headlight & Lantern Co., Inc. 455 Rochester Street Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797 starheadlight.com in f



PROUDLY MADE IN THE U.S.A. An ISO 9001:2015 Certified Company

2 Ш