



STAR HEADLIGHT & LANTERN CO.



- Auxiliary warning light kit
- Increased safety of children boarding or leaving the bus when stopped
- The two red LED lights above the front and rear bumpers are enhanced with this new system to readily alert motorists of a stopped school bus
- · These kits are school bus specific and come in Red
- Added flasher can be also used for other units in your fleet (ex. service trucks)

BKSCHOOL











Constellation® Kit Includes

- BKDLITE-RR x 4 (lights)
- BKLD418-2 x 2 (control box)
- SWH-346-2 x 2 (wire harness)
- SWH-346-5 x 2 (wire harness)
- 60 ft. 2-conductor cable
- All hardware: fuse holder, fuse, weather-tight connectors, tie wraps







check out the video



Hardware Kit Includes

- DLITE-RR x 4 (lights)
- 20 ft. 4-conductor cable
- 60 ft. 2-conductor cable
- All hardware: fuse holder, fuse, weather-tight connectors, tie wraps

STANDARD INSTALLATION

■ Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF218 Rev 12-08-2020





455 Rochester Street Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797

starheadlight.com



lin







STAR HEADLIGHT & LANTERN CO.

Class II



240SFL-C

- · Star Generation IV LEDs
- · 26 customer selectable flash patterns, including
- · Shipped in a quad flash pattern
- · Extremely low current draw
- · Rugged die-cast base is fully gasketed
- Permanent mount, 1" pipe mount, flange mount, magnet mount

266TSL-C

Class I



266TSL-C

- Star X-Fire[™] technology
- 12 different selectable flash patterns in either of two phases, plus steady-on
- S-Link System[™] synchronizing capabilities with other Star LED units, hardwire only
- · Extremely low current draw
- · Durable polycarbonate, twist on/off lens
- Lightweight polycarbonate, flange three-hole permanent mount, 1" pipe mount

256TSL-C

Class II



256TSL-C

- ·26 customer selectable flash patterns, plus steady-on
- Star Generation IV LEDs
- Extremely low current draw
- ·Lightweight polycarbonate base, flange three-hole permanent mount, 1" pipe mount

DLITE-RR

Class I



DLITE-RR

- Six super bright Star Generation V LEDs
- •S-Link System™ synchronizing capabilities with other Star LED units
- ·Robust design
- Rugged die-cast base
- Standard four wire hook up (power, ground, pattern, sync)
- Approvals: SAE Class I, CA Title 13 available where applicable

DH-363/LDH-36





- LDH-363
- · High intensity Star Generation IV LEDs are self-contained
- ·Steady-burn or flashing LED heads with built in flashers
- •S-Link System™ synchronizing capabilities with other Star LED units
- The high efficiency optics are available in three options: Spot, Trapezoidal, and Wide Spread
- · Quick install in any situation



- · Industry standard mounting footprint
- Polarity protected
- •Connections: 12" Red wire with 16-18 AWG butt splice, 3" wire with 1/4" ring terminal
- ·Glass filled nylon housing
- •SAE J994





Star Headlight & Lantern Co., Inc.

455 Rochester Street Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797 starheadlight.com



lin



PROUDLY MADE IN THE U.S.A. An ISO 9001:2015 Certified Company